

THIS UNIT CONTAINS
NASON ACRYLIC LACQUER THINNER
481-16™

Manufacturer:

*E.I. du Pont de Nemours & Co.
Du Pont Performance Coatings
Wilmington, DE 19898*

Telephone:

<i>Product information:</i>	<i>800-441-7515</i>
<i>Medical emergency:</i>	<i>800-441-3637</i>
<i>Transportation emergency:</i>	<i>800-424-9300</i>

PRODUCT INFORMATION

Acetone, Ethylbenzene (0.4-1.0%*@), Methyl alcohol(20%*@),
Toluene (30-30%*@), Vm&p naphtha, Xylene (3-4%*@)
GAL WT: 6.81 WT PCT SOLIDS: 0.00 VOL PCT SOLIDS: 0.00
SOLVENT DENSITY: 6.81 VOC LE: 6.9 VOC AP: 4.4
FLASH POINT: Below 20° F H: 2 F: 3 R:0 OSHA STORAGE: 1B
TSCA STATUS: In Compliance PHOTO-CHEMICALLY REACTIVE: YES

Caution:

- Provide sufficient ventilation.
- This material is extremely flammable.
- Keep away from heat sparks and flame.
- Prevent buildup of vapors.
- Close container after each use.
- Ground containers when pouring.
- Do not breathe vapors or mists.
- Protect eyes, skin and clothing.
- Wash thoroughly after handling and before eating or smoking.

Potential Health Risks:

- Inhalation: May cause nose and throat irritation. May cause nervous system depression, characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.
- Ingestion: May result in gastrointestinal distress
- Skin or Eye Contact: May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.