

DuPont™ 18258S™

Solventborne Cleaner – High Temperature

Type


DuPont™ 18258S™ is a multi-use cleaning solvent.

Description

DuPont™ 18258S™ is a solvent blend suitable for cleaning substrates and equipment used in polyurethane and epoxy coating operations. This is formulated to be effective in hot, humid conditions.

Recommended Uses


DuPont™ 18258S™ is recommended for a wide range of surface preparation and final paint cleaning applications. Due to the potential for static generation, it is not recommended for use directly on fiberglass or gelcoat. For fiberglass or gelcoat, DuPont™ 18248S™ Low VOC Waterborne Cleaner may be used to avoid static generation.



General Information for Use

Components

DuPont™ 18258S™ Solventborne Cleaner



Mix Ratio

Ready to use.

Factory-Packaged Cleaner

Color	Clear
Closed Cup Flash Point	Below 70°F (21°C)
Shelf Life	3 years (Unopened at 50° – 110°F)
Gallon Weight	6.5 lbs/gal

Physical Properties

VOC	Less Exempt (LE)	As Packaged (AP)
DuPont™ 18258S™ Solventborne Cleaner	6.5 lbs/gal	6.5 lbs/gal

Safety and Handling

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and MSDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Do not allow material to enter drains or waterways.

E-R 4686/K-17179
Revised 8/2010